Serial No. 10/840,205 Filed: 05/06/2004 Inventor: Banas, et al. Attorney Docket: 6006-157 Customer No. 29,335

This Claim Listing replaces all prior versions of claim listings in the application.

Claim Listing:

What is claimed is:

- 1. (Previously Amended) An implantable medical graft, comprising:
 - a. a generally tubular body member comprising a film selected from the group consisting of metallic and pseudometallic materials and having a luminal wall surface, an abluminal wall surface and a thickness intermediate the luminal wall surface and the abluminal wall surface; and b. at least a portion of the body member having a plurality of continuous circumferential undulations, with peaks and valleys, formed in each of the luminal wall and abluminal wall surfaces of the body member.
- 2. (Previously Amended) The implantable medical graft according to Claim 1, further comprising a plurality of microperforations passing through the thickness of the body member and communicating between the luminal surface and the abluminal surface.
- 3. (Original) The implantable medical graft according to Claim 1, wherein the film is made of a metallic material selected from the group consisting of titanium, vanadium, aluminum, nickel, tantalum, zirconium, chromium, silver, gold, silicon, magnesium, niobium, scandium, platinum, cobalt, palladium, manganese, molybdenum and alloys thereof.
- 4. (Original) The implantable medical graft according to Claim 2, further comprising at least one of a plurality of non-undulated circumferential regions of the body member.

17244 -2-

Serial No. 10/840,205 Filed: 05/06/2004

Inventor: Banas, et al. Attorney Docket: 6006-157

Customer No. 29,335

5. (Original) The implantable medical graft according to Claim 4, further comprising at least one of a plurality of suturing openings passing through the

wall thickness of the at least one of a plurality of non-undulated regions of the

body member.

6. (Original) The implantable medical graft according to Claim 4, wherein the

wall thickness of the undulating regions is less than the wall thickness of the non-

undulating regions.

7. (Original) The implantable medical graft according to Claim 6, wherein the

thickness of the undulating regions is between about $3-7 \mu m$ and the wall

thickness of the non-undulating regions is between about $10-20 \mu m$.

8. (Original) The implantable medical graft according to Claim 7, wherein the at

least a portion of a non-undulating region further comprises at least one of a

plurality of suturing openings passing through the wall thickness.

9. (Original) The implantable medical graft according to Claim 8, wherein the at

least one of a plurality of suturing openings further comprises a generally

cruciform-shaped slot pattern.

10. (Original) The implantable medical graft according to Claim 8, wherein the at

least one of a plurality of suturing openings further comprises a generally Y-

shaped slot pattern.

11. (Original) The implantable medical graft according to Claim 4, further

comprising at least one of a plurality of radially projecting barb members.

17244 -3-

Serial No. 10/840,205 Filed: 05/06/2004 Inventor: Banas, et al.

Attorney Docket: 6006-157 Customer No. 29,335

12. (Original) The implantable medical graft according to Claim 4, further comprising at least one of a plurality of suture members integrally extending

along a longitudinal axis of the body member.

13. (Previously Amended) A method of making an implantable medical graft

comprising the steps of:

a. providing a generally cylindrical substrate having a plurality of

circumferentially extending continuous undulations with peaks and

valleys, patterned along at least a portion of a longitudinal axis of the

generally cylindrical substrate;

b. vacuum depositing a graft-forming material onto the generally

cylindrical substrate; and

c. releasing the deposited graft-forming material from the substrate.

14. (Original) The method according to Claim 13, wherein the graft-forming

material is selected from the group consisting of biocompatible metals and

pseudometals.

15. (Original) The method according to Claim 13, further comprising the step of

forming a plurality of microperforations passing through the thickness of the

deposited graft-forming material.

16. (Original) The method according to Claim 13, further comprising the step of

forming at least one of a plurality of suturing openings through the wall thickness

of at least one non-undulating region of the deposited graft-forming material.

17244 -4-